

ISGUS Terminal IT 402



Access control is the primary element in any security concept. Security management systems protect employees, buildings, office equipment, stock and intellectual property.



IT 402 for Access Control

- » Terminals for access control with contact free identification
- » Operation via transponder with reading distance of 1 - 3 cm
- » Door opening function also in offline mode via system number check
- » Status display and booking acknowledgment via LED and acoustic signal
- » Integrated potentialfree contact for door opening

- » Anti-tamper alarm device via case contact
- » Connection via RS 485 (2-wire) to ISGUS Access Control Manager IT 8001, ACM 40xx or ACM 400
- » Suitable for outdoor environments
- » Multi-company feature for up to 10 different companies (as an option)
- » Easy and flexible installation

Technical Information IT 402



Badge reader systems

- » ISGUS-Prox
- » Hitag
- » LEGIC
- » Mifare

Voltage

- » External power supply unit:
8 - 12 V AC or
12 - 16 V DC

Current consumption

- » 0,2 A

Protection type

- » IP 65 on front side

Protection class

- » III / EN 60950

Environment

- » No direct sunlight
- » Ambient temperature: -10° C to +50° C

Rel. humidity

- » Max. 85 % (non condensing)

Data communication

- » RS 485, 2-wire

Weight

- » Approx. 0,2 kg

Dimensions

- » Ø 100 mm
- » Depth: 25 mm



ISGUS GmbH
Oberdorfstr. 18 - 22
78054 Villingen-Schwenningen

Tel. +49 7720 393-0
Fax +49 7720 393-184

info@isgus.de
www.isgus.de