

ISGUS Terminal IT 900



- Terminals of the IT 900 series are PC based terminals for time recording and plant data collection. In addition they can be used as foyer terminals / info stations and as update terminals.
- Along with recording of IN / OUT bookings, users can have access to personal information transferred via e-mail to his place of work.
- Users also have the opportunity to display holiday schedules, general time accounts, IN / OUT statuses or individual bookings.
- The terminals IT 900 / IT 920 can also be used for plant data collection (PDC). Via touchscreen the selection of information related to jobs is displayed: cost centre, machine no., working station, job status, work progress, etc.
- Data transmission is made via TCP/IP (Ethernet).
- If authorized, the user is able to update his bookings directly or insert forgotten bookings.
- Using JAVA technology, the employee's home language is selectable for the operator's guide, providing help for all terminal functions.
- The terminals are provided with a very clear and easy to read backlit display. The full graphic display consists of a touch screen and a TFT monitor with a resolution of 640 x 480 VGA.
- The terminal IT 900 provides a display size of 6,5" and the IT 920 of 10,4".





Technical Data IT 900

Badge reader systems:	ISGUS proximity, Hitag 1, Legic and SimonsVoss		
Voltage:	115 V / 230 V DC voltage		
Current consumption:	120 mA		
Protection type: Protection class:	IP 20 I / EN 60950		
Environment:	Ambient temperature: 0° to + 40° C No direct sunlight		
Rel. humidity:	max. 85 % (non condensing)		
Data communication:	Ethernet, 10 / 100 Mbit, TCP/IP		
Weight:	Approx. 1,5 kg - 2,3 kg depending on model		
Dimensions:	IT 900: Height: 230 mm	Width: 193 mm	Depth: 82 mm
	IT 920: Height: 255 mm	Width: 255 mm	Depth: 105 mm

subject to technical modifications

